

BROCHURE



P2010

Single-Engine Aircraft



Soar Higher



QUALITY AIRCRAFT SINCE 1948

TECNAM

The innovative four-seat single

The state-of-the-art TECNAM P TwentyTen is the most advanced high-wing, modern single-engine aircraft in the marketplace. Balanced controls. Unsurpassed stability.

The introduction of the P TwentyTen MkII satisfies the needs of even the most demanding and discerning private owners, offering superior performance as well as the most up-to-date avionics suite from GARMIN.

Cut through the air with speed, ease and efficiency in the TECNAM P2010, thanks to its aerodynamic shape, gently upswept wings and sculpted cowling.

This four seat aircraft brings together an advanced technology all carbon fibre fuselage with a metal wing, stabilator, an expansive cabin featuring ergonomic front and rear seats with exceptional legroom. The access to rear seats is made easy through a separate third entry door.

The wide composite cabin allows for a large instrument panel with state-of-art avionic options: twin touch screen G1000 NXi IFR flat-panel suite with integrated GFC700 autopilot.

Innovation has always been in Tecnam's DNA, the P2010 represents tangible proof.





“Manufacturing an aircraft is not just a job, it is a challenge for perfection, driven by infinite passion and dedication.”

Paolo Pascale Langer, CEO



Make your Choice

The latest technology, composite fuselage, metal wings, landing gear and stabilator make this aircraft ultra-modern and efficient. A large cabin, low maintenance cost and design-in safety add to the overall desirability of the P2010. Choose among 4 types of powerplant, including MoGas, AvGas, Jet A-1 and Diesel. Ask your Representative for more info.

Powerplant	P2010 180 HP	P2010 215 HP
Engine Manufacturer	Lycoming IO-360	Lycoming IO-390-C3B6
Engine Power	180 HP	215 HP
Propeller	2/3 Bladed Fixed/Variable pitch propeller	3 Bladed VP Propeller
Fuel Consumption	10 USg/hr (38 lt/hr) (@65%MCP - 2350 RPM)	11 USG/h (42 lt/h)
Fuel Type	AvGas grade 91/96 or 100 LL (ASTM D910)*	Avgas
Fuel Tank Capacity	64 US Gal (240 lt)	64 US Gal (240 lt)

* For additional information, refer to Lycoming Service Instruction No. 1070, latest issue.

The P2010, in all its versions, guarantees great performance and low CO₂ emissions. Tecnam has been the first manufacturer to approve an unleaded automotive fuel with the IO-360M1A engine as an option on the P2010.

Discover our commitment to sustainable actions



Design Weight and Loading

	P2010 180 HP	P2010 215 HP
Maximum Take-Off Weight	2,557 lb - 1,160 kg	2,557 lb - 1,160 kg
Empty Weight, Standard	1,687 lb - 765 kg	1,720 lb - 780 kg
Useful Load	870 lb - 395 kg	837 lb - 380 kg
Baggage Allowance	88lb - 40 kg	88lb - 40 kg

Performance

	P2010 180 HP	P2010 215 HP
Max Cruise Speed KTAS	137 kts - 254 km/h	140 kts - 259 km/h
Stall Speed (Flaps Down Power Off) KCAS	52 kts - 96 km/h	52 kts - 96 km/h
Max Operating Altitude	12,000 ft - 3,658 m	14,000 ft - 4,267 m
Take-Off Run	1,102 ft - 336 m	1,060 ft - 323 m
Take-Off Distance	1,952 ft - 595 m	1,549 ft - 472 m
Rate of Climb	841 ft/min - 4.27 m/sec	1,105 ft/min - 5.61 m/sec
Landing Run	778 ft - 237 m	778 ft - 237 m
Landing Distance	1,709 ft - 521 m	1,709 ft - 521 m
Range	530 nm - 982 km	530 nm - 982 km



Standard equipment

Garmin G1000 Nxi

G1000 Nxi Integrated Flight Deck System, includes:

- GDU 1050 10-inches PFD
- GDU 1054 10-inches MFD
- Dual GEA 71B Engine & Airframe unit
- Dual GIA 64WAAS Com/nav/GPS/GS/Loc
- GMA1360 Digital audio system
- GMU44B Magnetometer
- GDC72 Air data computer
- GRS79 AHRS
- GTP59 OAT
- GTX345R Mode S Transponder (ADS-B In and OUT)
- GFC 700 Autopilot Including Electronic Stability & Protection (ESP)

Flight instruments and indicators

- Magnetic Compass
- MD 302 Standby Attitude Module
- Pitot System Heated
- Static System
- Alternate Static Source
- Stall Warning Audible
- Stabilator Trim Position Indicator
- Rudder Trim Position Indicator

Flight controls

- Hydraulic Toe Brakes
- Parking Brake
- Electrical Flaps
- Dual Flight Controls
- Castering Nose Wheel
- Aileron Lock and Elevator Lock
- Flight Trim Controls:
 - Rudder with Indicator
 - Stabilator with Indicator
- Engine Controls:
 - Throttle
 - Mixture (only Lycoming)
 - Alternate Air
 - Fuel Control Selector with LH/RH/OFF

Electrical system

- Alternator, 28 Volt, 60 Amp
- Battery, 24 Volt 8.0 AH
- Rocker Switches:
 - Master Switch
 - Fuel Pump
 - Landing Light
 - Taxi Light
 - Navigation Lights
 - Strobe Light

- External Power Supply Receptacle
- Circuit Breaker Panel
- Static Discharge Wicks
- Landing/Taxi Light LED

Interior

- Pilot and Co-Pilot Seats Leather:
 - Adjustable Fore and Aft
 - Electric Vertical Adjustment
- Two Rear Passenger Seats Leather
- Seat Belts & Shoulder Harness, All Seats
- Wall To Wall Carpeting
- Hand Held Fire Extinguisher
- Map & Storage Pockets
- USB socket Type C
- Radio Call Plate
- Tow Bar
- Soundproofing
- Luggage Compartments
- Overhead Cockpit Speaker
- Four Position Intercom System
- First Aid Kit

Powerplant and Propeller

- Lycoming IO-360-M1A Engine 180 HP @ 2700 RPM
- Fuel Injection System
- Tubular Steel Engine Mount
- Dynafocal Rear Mount
- Engine Driven Vacuum Pump
- Alternate Engine Air
- Oil Cooler
- Shock Mounted Cowling
- Throttle Control
- Mixture Control
- Dual Ignition System, Shielded Magneto Engine Exhaust Muffler
- Fixed Pitch 2 Blade MT Propeller
- Propeller Spinner
- Electric Starter

Fuel system

- Two Integral Fuel Tanks With 240 Litres (64 UsGal) Total Capacity
- Engine Driven Fuel Pump
- Auxiliary Fuel Pump, Electric
- Fuel Tank Quick Drain
- Fuel Selector Valve, Left/Right/Off

Exterior

- Epoxy Corrosion Proofing, All Structure
- LH/RH Front Door Pilot/Co-Pilot, Lock and Key
- Rh Rear Door Passenger
- Rh Baggage Door With Lock

- Rear Window
- All Lateral Windows Tinted
- Fixed Landing Gear
- White Polyurethane Exterior Paint
- Tie Down Rings
- Main Wheels, 6.00 X 6
- Nose Wheel, 5.00 X 5

Exteriors lights

- Nav. Lights LED with Strobe Aveo Full LED TSO
- Landing/Taxi Light LED

Cabin comfort system

- Windshield Defroster
- Ventilator adjustable, 4 Place
- Heating System
- Soundproofing
- Cabin Monoxide Detection System

Product Support/Documents

- Manufacturer's Full Two Year Limited Warranty
- Pilot's Operation Handbook
- Maintenance Manual
- Parts Catalog
- Aircraft Log Book
- Engine Log Book

Standard Avionics Package

Also includes:

- Altitude Encoder
- Avionics Master Switch
- Mic & Phone Jacks Pilot/Copilot/Passengers
- Hand Held Microphone
- Avionics Circuit Breaker Panel
- Pilot And Co-Pilot PTT
- ELT 406

Antennas

- Marker Beacon Antenna
- Transponder Antenna
- VHF Antenna
- NAV Antenna
- Emergency Locator Transmitter Antenna





When we design an aircraft, we don't look at our heritage to check what we have already done, we look to our future to determine what we still need to do."

Giovanni Pascale Langer, Managing Director



Contact us or find us online

 +1 (863) 655-2400

 sales.usa@tecnam.com
info@tecnam.com

 www.tecnam.com



Specifications, weights, representations, colors, list of equipment, use of materials and model references listed herein are not warranted or guaranteed to be true or accurate. Actual useful load will vary depending on options installed on the aircraft. Always consult specific aircraft weight and balance parameters and data for flight planning. The pictures contained in this brochure of specific models or other products may contain optional equipment or nonstandard features, which even if available may be at an additional cost. Some optional equipment may require separate paid subscriptions from third-party providers. You may rely only upon statements and representations contained in actual contracts that you enter into with TECNAM. Referenced TECNAM trademarks are owned by Costruzioni Aeronautiche TECNAM SpA or its subsidiaries. All other brands, product names, company names, trademarks and service marks are the properties of their respective owners. All rights reserved. ©2021, Costruzioni Aeronautiche TECNAM SpA.



Costruzioni Aeronautiche Tecnam SpA
via Maiorise 81043 Capua (CE) - Italy